

DD-6 High Volume Pump

Engine Specifications:

Make/Model	HATZ 1D81Z 10.05 HP@2000 rpm
Engine Displacement	40.70 Cubic inches (0.666 liters)
Engine Type	One Cylinder, Air-Cooled, Diesel
Standard Equipment	Instrument Control Panel w/Hour Meter
Safety Shutdowns	Low Oil Pressure



Pump Specifications:

Pump Casing	A-36 Steel
Pump Capacity	600 GPM @ 5ft of Suction
Solid Handling	4.25 inch (107.95 mm)
Suction & Discharge Value Seats	Stainless Steel, 3/8" Plate
Flapper Valves	Weighted, Full-Flow Reinforced Rubber
Axle Type	3,500 LBS Torflex
Wheels & Tires	15 inch P205/75R15 Radial Tires
Max CFM	80-90

Max Operating Temperature	120° F / 48.88° C
Max Suction Lift	28 Feet (8.54m)
Max Operating Speed	65-70 RPM (Gearbox) 2000 RPM (Engine)
Max Pressure Max Working Pressure	100 PSI 59 PSI or 130 TDH
Max Operating Time	216 Hours (9 Days)
Fuel Consumption	6 - 7 Gallons/Day
Continuous Run Time	24 hours

Order at MyersSethPumps.com
or Contact MSP Sales at **904-389-6114**

Frame Specifications:

Frame Construction	10-inch Square Tubing
Fuel Capacity	71.0 U. S. Gallons (246.05L)
Lifting Bale	Heavy Duty Single Point
Tie Downs	(4) Heavy Duty D-Rings
Height	64 inches (162.56 cm)
Width	74 inches (187.96 cm)
Length	112 inches (284.48 cm)
Weight	1950 lbs (884.50 kg)



Standard Features Include:

- Heavy Duty Battery and Cables
- Camlock Hose Fittings
- Lockable Fuel Cap
- Fuel Gauge
- Heavy Duty Lifting Bale
- 5,000 lbs Front Jackstand
- Powder-Coated Frame
- DOT Trailer Lights
- High Volume Pump
- Easy Access Cleanouts

Optional Features Include:

- Highway Fenders
- Skid Mounted
- AUTO Start Control Panel
- GPS Telematics
- Pushrod Protection Cover

